

## Decodeur 802 Fire rated 30 min



<b>Model</b>	802 flat door
<b>Functionality</b>	30 minutes Fire rated
<b>Firerating</b>	30 minutes Fire rated according to BS - EN 1634 - 1
<b>Soundproofing</b>	Doorleaf value: Rw = Aprox. 27dB
<b>Imperial sizes</b>	44 mm Doorthickness: 1981 x 686 mm (27), 1981 x 762 mm (30), 1981 x 838 mm (33), 2032 x 813 mm (32), 2032 x 864 mm (34)
<b>Metric sizes</b>	44 mm Doorthickness 2040 x 626 mm, 2040 x 726 mm, 2040 x 826 mm
<b>Performance</b>	Flush internal door
<b>Edgeversion</b>	Seamless glued hardwood lipping at vertical sides
<b>Edgefinishing</b>	Unfinished
<b>Edge color suggestions</b>	Black woodgrain: RAL 9003 Grey vicenza oak: S 4005-Y20R Beige grey lorenzo oak: S 3005-Y20R Grey nebraska oak: S 5005-Y20R
<b>Doorweight</b>	thickness 44 mm: 22 kg/m2

**Doordesign** Black woodgrain, Grey vicenza oak, Beige grey lorenzo oak, Grey nebraska oak

**Remark** Pictured door is 762 x 1981 mm, position of the milling lines may be differ by other doorsizes. Due to the incidence of light, the milling lines can optically have a different appearance per position

**Photo** Detail